



LIFAIR air Top

DIMENSIONS	DN25-300
OPERATING TEMPERATURE AREA	0-120°C
PRESSURE CLASS	PN10
TEST PRESSURE	PN16
FILTER	AISI 304
BODY	St35.8 or St37.0
WELDING	St35.8 or St37.0
SEALING	COPPER
FLANGES	DIN2633

DN	25	32	40	50	65	80	100	125	150	200	250	300
Type W	220025	220032	220040	220050	220065	220080	220100	220125	220150	220200	220250	220300
Type F	221025	221032	221040	221050	221065	221080	221100	221125	221150	221200	221250	221300
D(mm)	33,7x2,6	42,4x2,6	48,3x2,6	60,3x2,9	76,1x2,9	88,9x3,2	114,3x3,6	139x4	168,3x4,5	219,1x4,5	273x5,0	324x5,6
H	512	512	512	654	654	684	684	850	850	1250	1250	1250
Ød	114,3	114,3	114,3	168,3	168,3	219,1	219,1	324	324	324	508	508
L	315	315	315	369	369	417	417	500	500	500	750	750
F	395	395	395	459	459	517	517	610	610	610	850	850
h1	332	332	332	460	460	476	476	550	550	900	900	900
h2	180	180	180	194	194	208	208	300	300	350	350	350
weight kg W	5	5	5	14,5	14,5	25,0	25,0	45	46	60	170	170
weight kg F	7	8	8	20	21	32	34	57	61	82	200	215
Volume L	3,2	3,2	3,3	8,9	9,0	19,0	19,2	65	65	80	200	200

LIFINATA UAB
lifin@lifin.lt

PLANMIX OY
Planmix@planmix.fi