



LIFAIR Trap air/dirt

DIMENSIONS

OPERATING TEMPERATURE AREA

PRESURE CLASS

TEST PRESSURE

FILTER

BODY

WELDING

SEALING

DN25-250

TypeW-welding

0-120°C

TypeF-flange DIN2633

PN10

PN16

AISI 304

St35.8 or St37.0

St35.8 or St37.0

COPPER

DN	25	32	40	50	65	80	100	125	150	200	250
Type W	230025	230032	230040	230050	230065	230080	230100	230125	230150	230200	230250
Type F	231025	231032	231040	231050	231065	231080	231100	231125	231150	231200	231250
D(mm)	33,7x2,6	42,4x2,6	48,3x2,6	60,3x2,9	76,1x2,9	88,9x3,2	114,3x3,6	139x4	168,3x4,5	219,1x6,3	273x6
H	806	806	806	966	966	996	996	1190	1190	1330	1760
Ød	114,3	114,3	114,3	168,3	168,3	219,1	219,1	324	324	406	508
L	315	315	315	369	369	417	417	500	500	660	750
F	395	395	395	459	459	517	521	610	610	760	850
h1	332	332	332	460	460	476	476	516	516	630	800
h2	424	424	424	456	456	470	470	625	625	700	900
Weight kg W	10	10	10	18	18	31	31	80	80	125	230
Weight kg F	12	13	13	23	24	38	40	92	95	150	260
Volume L	4	4	4	12	12	26	26	80	80	150	300

LIFINATA UAB

lifin@lifin.lt