



**LIFAIR Trap air/dirt with a flanged bottom cup**

DIMENSIONS

OPERATING TEMPERATURE AREA

PRESURE CLASS

TEST PRESSURE

FILTER

BODY

WELDING

SEALING

DN25-250

0-120°C

PN10

PN16

AISI 304

St35.8 or St37.0

St35.8 or St37.0

COPPER

TypeW-welding

TypeF-flange DIN2633

DN	25	32	40	50	65	80	100	125	150	200	250
Type W	240025	240032	240040	240050	240065	240080	240100	240125	240150	240200	240250
Type F	241025	241032	241040	241050	241065	241080	241100	241125	241150	241200	241250
D(mm)	33,7x2,6	42,4x2,6	48,3x2,6	60,3x2,9	76,1x2,9	88,9x3,2	114,3x3,6	139x4	168,3x4,5	219,1x6,3	273x6,3
H	756	756	756	916	916	946	946	1140	1140	1330	1700
Ød	114,3	114,3	114,3	168,3	168,3	219,1	219,1	324	324	406	508
L	315	315	315	369	369	417	417	500	500	660	750
F	395	395	395	459	459	517	521	610	610	760	850
h1	332	332	332	460	460	476	476	516	516	630	800
h2	424	424	424	456	456	470	470	625	625	700	900
weight kg W	18	18	18	32	32	53	53	125	125	175	350
weight kg F	20	21	21	37	38	60	62	137	140	200	395
Volume L	3,2	3,2	3,3	8,9	9,0	19,0	19,2	65	65	150	300

LIFINATA UAB

[lifin@lifin.lt](mailto:lifin@lifin.lt)