



LIFAIR Trap air/dirt

DIMENSIONS

OPERATING TEMPERATURE AREA

PRESURE CLASS

TEST PRESSURE

FILTER

BODY

WELDING

SEALING

DN25-300

TypeW-welding

0-120°C

TypeF-flange DIN2633

PN10

PN16

AISI 304

St35.8 or St37.0

St35.8 or St37.0

COPPER

DN	25	32	40	50	65	80	100	125	150	200	250	300	300/10
Type W	260025	260032	260040	260050	260065	260080	260100	260125	260150	260200	260250	260300	26030010
Type F	261025	261032	261040	261050	261065	261080	261100	261125	261150	261200	261250	261300	26130010
D(mm)	33,7x2,6	42,4x2,6	48,3x2,6	60,3x2,9	76,1x2,9	88,9x3,2	114,3x3,6	139x4	168,3x4,5	219,1x6,3	273x6,3	323,9x7,1	323,9x7,1
H	756	756	756	916	916	946	946	1140	1140	1330	1700	1700	2020
Ød	114,3	114,3	114,3	168,3	168,3	219,1	219,1	324	324	406	508	508	610
L	315	315	315	369	369	417	417	500	500	660	750	750	850
F	395	395	395	459	459	517	521	610	610	760	850	850	1005
h1	332	332	332	460	460	476	476	516	516	630	800	800	985
h2	424	424	424	456	456	470	470	625	625	700	900	900	1035
weight kg W	10	10	10	18	18	31	31	80	80	125	230	230	470
weight kg F	12	13	13	23	24	38	40	92	95	150	260	275	515
volume L	4	4	4	12	12	26	26	80	80	150	300	300	500

LIFINATA UAB

lifin@lifin.lt