



LIFAIR Trap air/dirt HI-FLOW

DIMENSIONS

OPERATING TEMPERATURE AREA

PRESURE CLASS

TEST PRESSURE

FILTER

BODY

WELDING

SEALING

DN25-300

0-120°C

PN10

PN16

AISI 304

St35.8 or St37.0

St35.8 or St37.0

COPPER

TypeW-welding

TypeF-flange DIN2633

DN	25	32	40	50	65	80	100	125	150	200	250	300
Type W	280025	280032	280040	280050	280065	280080	280100	280125	280150	280200	280250	280300
Type F	281025	281032	281040	281050	281065	281080	281100	281125	281150	281200	281250	281300
D(mm)	33.7x2.6	42.4x2.6	48.3x2.6	60.3x2.9	76.1x2.9	88.9x3.2	114.3x3.6	139x4	168x4.5	219x4,5	273x5	324x5,6
H	1000	1000	1000	1250	1250	1250	1250	1600	1600	1850	2500	3100
Ød	114.3	114.3	114.3	168.3	168.3	219	219	324	324	508	508	610
L	315	315	315	369	369	417	417	500	500	700	750	850
F	395	395	395	459	459	517	521	610	610	820	850	1000
h1	454	454	454	628	628	628	628	800	800	850	1200	1500
h2	546	546	546	622	622	622	622	800	800	1000	1300	1600
Weight kg W	13	13	13	24	24	37	37	100	100	200	260	620
Weight kg F	15	16	16	29	30	44	46	112	115	222	290	665
Volume L	6	6	6	15	15	40	40	115	115	300	450	760

LIFINATA UAB

lifin@lifin.lt