



LIFAIR Trap dirt

FOR USE IN SEALED HEATING AND COOLING SYSTEMS.

DIRT SEPARATORS PROTECT THE BOILERS, PUMPS AND FITTINGS FROM DAMAGE CAUSED BY THE DEPOSIT OF DIRT PARTICLES.

CONTRARY TO FILTERS THE DIRT CAN BE REMOVED WHILE THE SYSTEM IS IN OPERATION.

DIMENSIONS	DN25-300
OPERATING TEMPERATURE AREA	0-150°C
PRESURE CLASS	PN16
FILTER	AISI 304
BODY	St35.8 or St37.0
WELDING	St35.8 or St37.0
SEALING	COPPER
FLANGES	DIN2633

DN	25	32	40	50	65	80	100	125	150	200	250	300
Type W	250025	250032	250040	250050	250065	250080	250100	250125	250150	250200	250250	250300
Type F	251025	251032	251040	251050	251065	251080	251100	251125	251150	251200	251250	251300
D(mm)	33,7x2,6	42,4x2,6	48,3x2,6	60,3x2,9	76,1x2,9	88,9x3,2	114,3x3,6	139x4	168,3x4,5	219,1x4,5	273x5,0	324x5,6
H	412	412	412	554	554	584	584	750	750	1200	1200	1200
Ød	114,3	114,3	114,3	168,3	168,3	219,1	219,1	324	324	324	508	508
L	315	315	315	369	369	417	417	500	500	500	750	750
F	395	395	395	459	459	517	517	610	610	610	850	850
h1	180	180	180	194	194	208	208	300	300	350	350	350
h2	232	232	232	360	360	376	376	450	450	850	850	850
Weight kg	5	5	5	14,5	14,5	25,0	25,0	45	46	60	170	170
weight kg F	7	8	8	20	21	32	34	57	61	82	200	215
Volume L	3,2	3,2	3,3	8,9	9,0	19,0	19,2	65	65	80	200	200

LIFINATA UAB

lifin@lifin.lt