



LIFAIR air HI-FLOW

DIMENTIONS DN25-300
 OPERATING TEMPERATURE AREA 0-120°C
 PRESSURE CLASS PN10
 TEST PRESSURE PN16
 FILTER AISI 304
 BODY St35.8 or St37.0
 WELDING St35.8 or St37.0
 SEALING COPPER
 FLANGES DIN2633

DN	25	32	40	50	65	80	100	125	150	200	250	300
Type W	270025	270032	270040	270050	270065	270080	270100	270125	270150	270200	270250	270300
Type F	271025	271032	271040	271050	271065	271080	271100	271125	271150	271200	271250	271300
D(mm)	33.7x2.6	42.4x2.6	48.3x2.6	60.3x2.9	76.1x2.9	88.9x3.2	114.3x3.6	139x4	168x4.5	219x4.5	273x5	324x5.6
H	756	756	756	916	916	946	946	1140	1140	1150	1700	2020
Ød	114.3	114.3	114.3	168.3	168.3	219	219	324	324	508	508	610
L	315	315	315	369	369	417	417	500	500	750	750	850
F	395	395	395	459	459	517	517	610	610	820	850	1005
h1	576	576	576	722	722	738	738	800	800	800	1350	1570
h2	180	180	180	194	194	208	208	340	340	350	350	450
Weight kg W	10	10	10	18	18	31	31	80	80	120	230	470
weight kg F	12	13	13	23	24	38	40	92	95	192	260	515
Volume L	4	4	4	11	11	26	26	80	80	120	300	500

LIFINATA UAB
lifin@lifin.lt

PLANMIX OY
Planmix@planmix.fi