



LIFAIR Trap air/dirt HI-FLOW with a flanged bottom cup

DIMENSIONS

OPERATING TEMPERATURE AREA

PRESURE CLASS

TEST PRESSURE

FILTER

BODY

WELDING

SEALING

DN25-200

TypeW-welding

0-120°C

TypeF-flange DIN2633

PN10

PN16

AISI 304

St35.8 or St37.0

St35.8 or St37.0

COPPER

DN	25	32	40	50	65	80	100	125	150	200
Type W	290025	290032	290040	290050	290065	290080	290100	290125	290150	290200
Type F	291025	291032	291040	291050	291065	291080	291100	291125	291150	291200
D(mm)	33.7x2.6	42.4x2.6	48.3x2.6	60.3x2.9	76.1x2.9	88.9x3.2	114.3x3.6	139x4	168x4.5	219x6.3
H	1000	1000	1000	1250	1250	1250	1250	1600	1600	1850
Ød	114.3	114.3	114.3	168.3	168.3	219	219	324	324	508
L	315	315	315	369	369	417	417	500	500	700
F	395	395	395	459	459	517	521	610	610	820
h1	454	454	454	628	628	628	628	800	800	850
h2	546	546	546	622	622	622	622	800	800	1000
Weight kg W	20	20	20	36	36	58	58	135	135	330
Weight kg F	22	23	23	41	42	65	67	147	150	352
Volume L	6	6	6	15	15	40	40	115	115	230

LIFINATA UAB

lifin@lifin.lt

PLANMIX OY

Planmix@planmix.fi